

HMI Server with WiFi


Feature

- Supports Display on cMT Viewer Clients
- Compact Design and DIN-rail Mountable
- Fan-less Cooling System
- Built-in 256 MB Flash Memory
- microSD Card Slot for Expansion of Storage
- One USB Host Port
- Supports MPI 187.5K
- Built-in Power Isolator
- WiFi compatible with 802.11 b/g/n
- cMT-SVR-202: Built-in EasyAccess 2.0 License

Memory	Flash	256 MB
	RAM	256 MB
Processor		Quad-core RISC
I/O Port	SD Card Slot	microSD x 1
	USB Host	USB 2.0 x 1
	USB Client	N/A
	Ethernet	10/100 Base-T x 1
	WiFi	IEEE 802.11 b/g/n 802.11b: max 19.52 dBm 802.11g: max 15.35 dBm 802.11n: max 15.28 dBm
	COM Port	COM1: RS-232 2W COM2: RS-485 2W/4W COM3: RS-485 2W
RTC		Built-in
Power	Input Power	24±20%VDC
	Power Isolation	Built In
	Power Consumption	450mA@24VDC
	Voltage Resistance	500VAC (1 min)
	Isolation Resistance	Exceed 50MΩ at 500VDC
Specification	PCB Coating	Yes
	Enclosure	Plastic
	Dimensions WxHxD	27 x 130 x 115 mm
	Weight	Approx. 0.18 kg
	Mount	35 mm DIN rail mounting
Environment	Protection Structure	IP20
	Storage Temperature	-20° ~ 70°C (-4° ~ 158°F)
	Operating Temperature	-20° ~ 55°C (-4° ~ 131°F)
	Relative Humidity	10% ~ 90% (non-condensing)
	Altitude	3,000 m
	Vibration Endurance	10 to 25Hz (X, Y, Z direction 2G 30 minutes)
Certificate	CE	CE marked
	UL	cULus Listed
Software	EasyBuilder Pro	V6.02.02 or later versions*
	Weincloud	cMT-SVR-200: EasyAccess 2.0 (Optional) cMT-SVR-202: EasyAccess 2.0 (Built-in)

*The minimum software requirement for units labeled as cMT-SVR-200 (V2) / cMT-SVR-202 (V2): EasyBuilder Pro V6.09.02.

Dimensions



a	WiFi	e	Power Connector
b	USB Host Port	f	microSD Card Slot
c	Ethernet Port	g	DIP Switch
d	COM1: RS-232 2W, COM2: RS-485 2W/4W, COM3: RS-485 2W		

Pin Assignment:
COM1 [RS232], COM2 / COM3 [RS485],
9 Pin, Male, D-sub

PIN#	COM1 [RS-232] 2W	COM2 [RS-485] 2W	COM2 [RS-485] 4W	COM3 [RS-485] 2W
1				Data+
2	RxD			
3	TxD			
4				Data-
5	GND			
6		Data+	Rx+	
7		Data-	Rx-	
8			Tx+	
9			Tx-	

Ordering Information

❑ cMT-SVR-200:

256 MB flash memory
 256 MB RAM on board
 10/100M Ethernet port x 1
 Antenna 2dBi, RP-SMA Plug connector
 Optional: RZACEA020 EasyAccess 2.0
 Activation Card

❑ cMT-SVR-202:

256 MB flash memory
 256 MB RAM on board
 10/100M Ethernet port x 1
 Antenna 2dBi, RP-SMA Plug connector
 Built-in EasyAccess 2.0 license

Contact: WEINTEK IIOT LTD. Web: www.weintekiiot.com

cMT-SVR-200_cMT-SVR-202_Datasheet_ENG_20250415